



Key Features:

- + 4.0 MP resolution high-definition video
- + 2688 x 1520 @ 30 fps
- + 4 mm lens offers 98° field of view
- + Supports H.265+, H.265, H.264+, H.264
- + Starlight Low-Light 0.005 Lux

4.0 Megapixel



4.0 MEGAPIXEL 270' IR H.265+ OUTDOOR BULLET IP SECURITY CAMERA

Get better storage and bandwidth with the latest in video compression technology

Take advantage of the latest H.265+ compression in this Alibi 4.0 Megapixel 270' IR Outdoor Bullet Security Camera to capture and store high-definition video, even in low light, like never before.

With its 1/2.5" Progressive Scan CMOS, this camera delivers 4.0 Megapixel resolution @ 30 fps (2688 x 1520), providing the level of detail needed for facial recognition and license plate identification.

H.265+ is the latest and greatest in video compression format that provides superior improvements in image quality and bandwidth. It also allows for faster, more fluid remote viewing, along with the ability to view more channels remotely. With H.265+ compression, you can store more information using fewer hard drives, which allows you to do more with less. This camera also supports H.265+, H.265, H.264+, H.264.

You can also dramatically reduce file sizes with this latest video compression format.

This camera's 0.008 low lux rating improving night-time performance. Specifically designed for surveillance in low-light environments, not only does it enhance clarity, it also offers color images for low-light applications.

In darkness, you can rely on the camera's full frame illumination technology to see clear, sharp images up to 270' in the dark. This technology delivers a wider illumination spread and offers several advantages over standard IR, such as clearer, brighter images in low light and at night, and reduces overexposure at the center of the image and eliminates hot spots.

What's Included:

- + (1) 4.0 MP IP IR Bullet Security Camera
- + (1) Mounting template
- + (1) Mounting hardware
- + (1) Quick start guide
- + Protection and Warranty:

SPECIFICATIONS

Image Type	Progressive Scan CMOS
Image Size (in)	1/2.5
Color	Yes
Camera Resolution (px)	2688 x 1520
Megapixel	4.0
Day/Night Function	True D/N w/Mechanical Cut Filter
Digital Noise Reduction (DNR)	3D DNR
Digital Range (dB)	120
Electronic Shutter	1/3s ~ 1/100,000s
Flip	Digital Horizontal/Vertical
IR Array Range (ft)	270
IR Wavelength (nm)	850
Lux (B/W)	0.0 (IR ON)
Lux (Color)	0.008
AGC Control	OSD Selectable
Wide Dynamic	Yes
Relative Aperature (F-stop)	F1.6
Focus	Fixed
Lens Mount	M12
Lens Type	Fixed
Max FOV (degrees)	88
Focal Length (mm)	4.0
Ethernet Interface	RJ-45
Ethernet Ports	1
Ethernet Speed	10/100
Protocols	TCP/IP, HTTP, HTTPS, DHCP, UDP, RTP, RTSP and more
Remote Configuration	Yes
Remote Viewable	Yes
Bit Rate	32Kbps ~ 16Mbps
Compression Type	H.265+, H.265, H.264, H.264+
Email Notification	Yes
Event Log	Yes
Event Notification	Yes
Selectable Frame Rate	Yes
Frame Rate (fps)	60Hz: 30fps (2048 × 1536, 1920 × 1080, 1280
Motion Detection	Yes
Privacy Video Block	Yes
SD Card Reader	Micro SD card (not included) up to 128 GB
Storage Capacity (GB)	Up to 128 (micro SD card not included)
Video Analytics Capable	Yes

Video Streaming	Tri
Dimensions	4.1" Dia. x 11.8"
SD Card Included	Micro SD card, (not included) up to 128 GB
Card Reader Type	Micro SD
Certification	UL & FCC, RoHS, CE
Construction	Metal
Mounting Bracket Included	Yes
Operating Humidity	0% ~ 95% (non-condensing)
Operating Temperature (F)	-22° ~ 140°
Product Color	White/Black
Product Color Outdoor	White/Black Yes
	,
Outdoor	Yes
Outdoor Ingress Protection	Yes IP67
Outdoor Ingress Protection Weight (lb)	Yes IP67 2.7
Outdoor Ingress Protection Weight (lb) PoE	Yes IP67 2.7 802.3af 12 VDC, 1 A, max: 11.5 W, PoE (802.3af, 36V to 57V), 0.4 A to
Outdoor Ingress Protection Weight (lb) PoE Power (w)	Yes IP67 2.7 802.3af 12 VDC, 1 A, max: 11.5 W, PoE (802.3af, 36V to 57V), 0.4 A to 0.2 A, max. 12.9 W
Outdoor Ingress Protection Weight (lb) PoE Power (w) Volts DC	Yes IP67 2.7 802.3af 12 VDC, 1 A, max: 11.5 W, PoE (802.3af, 36V to 57V), 0.4 A to 0.2 A, max. 12.9 W
Outdoor Ingress Protection Weight (Ib) PoE Power (w) Volts DC Browser Support	Yes IP67 2.7 802.3af 12 VDC, 1 A, max: 11.5 W, PoE (802.3af, 36V to 57V), 0.4 A to 0.2 A, max. 12.9 W 12 Internet Explorer, Safari